


Moulded End Caps




d	Z	I	SDR 17.6 - S 8.3 - PN6		SDR 11 - S 5 - PN10	
			S	Wt. in Kgs	S	Wt. in Kgs
20	45	35	-	-	1.9	0.01
25	52	40	-	-	2.3	0.01
32	58	44	-	-	2.9	0.02
40	67	50	-	-	3.7	0.03
50	75	55	-	-	4.6	0.05
63	85	62	-	-	5.8	0.09
75	95	63	-	-	6.8	0.13
90	110	79	-	-	8.2	0.23
110	127	88	6.3	0.30	10	0.40
125	138	102	7.1	0.40	11.4	0.62
140	144	106	8.0	0.60	12.7	0.82
160	154	109	9.1	0.70	14.6	1.06
180	191	141	10.2	0.75	16.4	1.73



Weld Type: Butt
Socket Weld End Caps & larger sizes available

Stub Flange / Adaptor



Weld Type: Butt

d	d ₃	d ₄	Z	SDR 17 S-8.3-PN6				SDR 11 S-5-PN10			
				h ₁	h ₃	S	Wt. in Kg	h ₁	h ₃	S	Wt. in Kg
20	26	51	50	-	-	-	-	7	30	2.0	0.01
25	30	58	50	-	-	-	-	9	28	2.3	0.02
32	38	64	50	-	-	-	-	10	27	3.0	0.04
40	44	70	50	-	-	-	-	11	24	3.7	0.06
50	54	81	50	-	-	-	-	12	23	4.5	0.1
63	68	95	50	-	-	-	-	14	16	5.7	0.1
75	78	107	50	-	-	-	-	16	14	6.8	0.2
90	96	126	80	-	-	-	-	17	43	8.2	0.3
110	116	158	80	18	37	6.6	0.3	18	37	10.0	0.4
125	132	158	80	18	42	7.4	0.3	25	35	11.4	0.5
140	155	188	80	18	34	8.3	0.5	25	27	12.7	0.7
160	165	212	80	18	34	9.5	0.6	25	27	14.5	0.9
180	180	212	80	20	30	10.7	0.6	30	20	16.4	0.9
220	232	268	100	24	36	11.9	1.4	32	28	18.2	2.0
225	235	268	100	24	46	13.4	1.2	32	38	20.5	1.8
250	285	320	100	25	35	14.8	2.0	35	25	22.7	2.9
280	291	320	100	25	45	16.6	2.2	35	35	25.5	3.2
315	335	370	100	25	35	18.7	2.5	35	25	28.6	3.6
355	373	430	120	30	50	21.1	3.9	40	40	32.3	5.7
400	427	482	120	33	42	23.7	5.2	46	29	36.4	7.6
450	514	585	120	46	14	26.7	10.1	60	35	40.9	14.2
500	530	585	120	46	24	29.7	12.6	60	25	45.5	16.2
560	615	685	120	50	10	33.2	13.3	60	40	50.9	18.5
630	642	685	120	50	30	37.4	12.6	60	29	57.3	15.3

* dimensions in mm